



PRODUCT:

PF-091-80-CF-00

REV052620

PRODUCT DESCRIPTION:

Vertical Lapped fire resistant fiber with compressed fiber, acoustical facing

FIBER

Physical Property	Description - Value	Tolerance
Material	FR Fiber blend	
Color	Grey	
Areal weight	1400 gsm @ 2" thick	+/- 10%
Service Temperature	-40 °F – 350 °F	
Flammability	Passes MVSS 302, UL HF1, UL HBF	
Glow wire ignition temp (GWIT)	700 °C (1292 °F)	
Glow wire flam. Index (GWFI)	750 °C (1382 °F)	

FACING

Physical Property	Description - Value	Tolerance
Material	Compressed acoustical fiber blend	
Color	Black	
Areal weight	300gsm	+/- 10%
Service Temperature	-40 °F – 180 °F	

Compliance Features:

- **UL94 HF-1 Listed File no. E504782**

*THE VALUES PRESENTED ARE TYPICAL AND ARE NOT INTENDED FOR SPECIFICATION PURPOSES. This information is provided without warranty, representation, inducement or license of any kind. INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE OR PURPOSE, except that it is accurate to the best of Technicon Industries' knowledge or obtained from sources believed by Technicon Industries to be accurate, and Technicon Industries does not assume any legal responsibility for the use or reliance upon same. Customers are encouraged to conduct their own tests for suitability and conformance.





PRODUCT:

PF-091-80-CF-00

REV052620

PRODUCT DESCRIPTION:

Vertical Lapped fire resistant fiber with compressed fiber, acoustical facing

FIBER

Physical Property	Description - Value	Tolerance
Material	FR Fiber blend	
Color	Grey	
Areal weight	1400 gsm @ 2" thick	+/- 10%
Service Temperature	-40 °F – 350 °F	
Flammability	Passes MVSS 302, UL HF1, UL HBF	
Glow wire ignition temp (GWIT)	700 °C (1292 °F)	
Glow wire flam. Index (GWFI)	750 °C (1382 °F)	

FACING

Physical Property	Description - Value	Tolerance
Material	Compressed acoustical fiber blend	
Color	Black	
Areal weight	300gsm	+/- 10%
Service Temperature	-40 °F – 180 °F	

Compliance Features:

- **UL94 HF-1 Listed File no. E504782**

*THE VALUES PRESENTED ARE TYPICAL AND ARE NOT INTENDED FOR SPECIFICATION PURPOSES. This information is provided without warranty, representation, inducement or license of any kind. INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE OR PURPOSE, except that it is accurate to the best of Technicon Industries' knowledge or obtained from sources believed by Technicon Industries to be accurate, and Technicon Industries does not assume any legal responsibility for the use or reliance upon same. Customers are encouraged to conduct their own tests for suitability and conformance.

